

KABEL BESKYTTELSE

8-11B

KONTRAMØTRIK
Af forniklet messing

LOCK-NUT
Of nickel-plated brass



Sekskantet forniklet messing kontramøtrik. Temperatur op til +200° C.

Hexagonal lock-nut of nickel-plated brass. Temperature range: Up to +200° C.

Metrisk gevind

S&K nr.	Gevind Mx1,5 EN 60423	Højde mm.	Nøglevidde	El nr.	EAN nr.
66-D4312109	M 12	3,0	15 mm.	8613 040 501	
66-D4316107	M 16	3,0	20 mm.	8613 040 514	
66-D4320104	M 20	3,5	24 mm.	8613 040 527	
66-D4325109	M 25	3,5	30 mm.	8613 040 530	
66-D4332107	M 32	4,5	35 mm.	8613 040 543	
66-D4340102	M 40	4,5	45 mm.	8613 040 556	
66-D4350101	M 50	5,5	55 mm.	8613 040 569	
66-D4363101	M 63	6,0	70 mm.	8613 040 572	

PG gevind

S&K nr.	Gevind DIN 40430	Højde mm.	Nøglevidde	El nr.	EAN nr.
66-D4007104	PG 7	2,9	15 mm.	-	
66-D4008101	PG 9	2,9	18 mm.	-	
66-D4011101	PG 11	3,1	21 mm.	-	
66-D4013105	PG 13.5	3,1	23 mm.	-	
66-D4016106	PG 16	3,1	26 mm.	-	
66-D4021100	PG 21	3,6	32 mm.	-	
66-D4029106	PG 29	4,1	41 mm.	-	
66-D4036104	PG 36	5,1	51 mm.	-	
66-D4042105	PG 42	5,6	60 mm.	-	
66-D4049104	PG 48	5,6	64 mm.	-	



SØRENSEN & KOFOED A/S

Smedeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk